

MAGNUM Outdoor Control Control cabinets

Complete watertight control cabinets manufactured and fitted according to the number of cables/mats and power. The system can be implemented in both 230V and 400V.

Connection box

The control cabinets can be assembled custom-made for each project. The standard version is equipped (according to NEN1010) with the necessary waterproof cable entries, magnetic circuits (relays), circuit breakers, earth leakage switches, terminal strips for easy connection of power and heating cables and the special outdoor road sensor units. For this, the diagram shown in the switch box must be followed.



Specifications

ETO2-4550 DIN-rail	Thermostat 0°C / +5°C 230V
2x ETOG-56 Sensorunits	Humidity & Temperature
Potential-free contacts	3 x 16 Amps
Required solenoid circuits (relays)	230V/400V
Required installation circuit breakers	16 Amps
Connection terminals	for mounting power cables
Indicator lights	
Warranty	2 year



Art.nr.	Description	kW	Cabinet dimensions	Unit	
900004	MAGNUM Outdoor control cabinet	3,6 kW	430 x 310 x 160 mm	units/1	incl. ETO2-4550 DIN-rail thermostat and 2x ETOG-56 sensor units
900010	MAGNUM Outdoor control cabinet	10 kW	500 x 400 x 200 mm	units/1	incl. ETO2-4550 DIN-rail thermostat and 2x ETOG-56 sensor units
900020	MAGNUM Outdoor control cabinet	20 kW	500 x 400 x 200 mm	units/1	incl. ETO2-4550 DIN-rail thermostat and 2x ETOG-56 sensor units
900030	MAGNUM Outdoor control cabinet	30 kW	700 x 520 x 253 mm	units/1	incl. ETO2-4550 DIN-rail thermostat and 2x ETOG-56 sensor units
900040	MAGNUM Outdoor control cabinet	40 kW	700 x 520 x 253 mm	units/1	incl. ETO2-4550 DIN-rail thermostat and 2x ETOG-56 sensor units
900050	MAGNUM Outdoor control cabinet	50 kW	700 x 520 x 253 mm	units/1	incl. ETO2-4550 DIN-rail thermostat and 2x ETOG-56 sensor units