- EV 22 kW charger
- LED indicator
- 5m cable
- Type 2 connector

| Product ID | MEV22NNNN5T2 |
|-----------------------------|--|
| Charging mode | Level 2 |
| Connector type | Type 2 connector with 5m cable |
| Charging control | Plug-and-Charge |
| Internet connection | No |
| External communication | RS485 |
| IP protection | IP55 |
| Impact strength | IK10 |
| Display | No |
| LED indicator | LED color indicators |
| Communication protocol | - |
| Background functions | - |
| Reports | - |
| Standard and CE certificate | |
| Leakage protection | TypeB (AC30mA + DC6mA) |
| Mounting | Wall / Stand |
| Stand / ground mount | Available, not included |
| Cooling method | Natural Cooling |
| Power network configuration | TN / TT -> (3P+N+PE), TN / TT -> (1P+N+PE) |
| Efficiency | >99% |
| Power meter | No |
| AC power Input rating | 3-phase 400V±20% / 1-phase 230V±20% |
| Rated frequency | 50/60 Hz |
| Output current | 32 A / 16 A |
| Output power | 22 kW/ 11 kW/ 7.4 kW |
| DLM function | Available, CT not included |
| Storage temperature | -40 to 75°C ambient |
| Operating temperature | -30 to 55°C ambient |
| Operating humidity | Up to 95% non-condensing |
| Altitude | ≤2000m |
| Electrical protection | Over/Under Voltage Protection, Over Load Protection, Short Circuit Protection, Earth Leakage Protection, Ground Protection, Over-temp Protection, Surge Protection |
| Dimensions mm | 455 (h) x260 (w) x150 (d) |
| Weight kg | 5,9 |
| Warranty | 24 months |





